United Umber Industries P.O.Box 40342, 6303 Larnaca, CYPRUS

MATERIAL SAFETY DATA SHEET

Crude Burnt Similloti

1. Chemical, Product and Company Identification

Manufacturer: UNITED UMBER INDUSTRIES

Address: P.O.Box 342, Larnaca 6303, CYPRUS

Tel: (357) 24 652231. Fax: (357) 24 651599.

Email: unumber@cytanet.com.cy

<u>Product Name:</u> Crude Burnt Similloti Date Revised: 10th October, 2010

2. Material Identification

 $\begin{array}{lll} Trade/Material\ name & : & Crude\ Burnt\ Similloti \\ Other\ Designations & : & No.\ 2-R-LL\ Cyprus \end{array}$

CAS Number : 12713-03-0

Chemical composition : $Fe_2O_3 + MnO_2 + SiO_2$

Iron Oxide + Manganite + Silica

3. Hazardous Ingredients

Mn compound 1.5

Silica 10

4. Physical Data

Appearance : Crude (not powdered) Mol. Wt: n.a. MP: n.a.

Vapour Dens. : n.a. Colour : Red

Density (ISO 787/9): n.a. B.P.: n.a. Solubility: Insoluble

Volatile % vol : n.a.

5. Fire and Explosion Data

Flash point : n.a. Flammable limits : n.a.

Extinguishing media: As appropriate for surrounding combustibles

6. Reactivity Data

Material is stable

Incompatibility: MnO2 is an oxidizer. It must not be heated or rubbed against easily

oxidizable materials.

If exposed to acids it can liberate hazardous gases

Hazardous decomposition products: none

7. Health Hazard Data

Risk Summary : Skin contact may cause mechanical irritation due to abrasion. Eye contact

will result in no specific effects other than general particulate irritation.

Not absorbed by the body.

Excessive exposure above the TLV can give pulmonary irritation.

Primary entry routs: Inhalation, ingestion.

Acute effects : Inhalation of dust may cause mechanical irritation to the respiratory tract.

Skin and eye contact may cause a mechanical abrasion irritation.

Chronic effects : Long term exposure to silica causes silicosis, a form of pulmonary fibrosis.

Continued exposure to silica can lead to cardiopulmonary impairment.

First Aid:

Eye Contact: Flush thoroughly with large amounts of water and consult medical help.

Skin Contact: Wash with soap and water.

Inhalation : Remove to fresh air and get medical help for any breathing difficulties.

Ingestion : Consume large amounts of water to induce vomiting and get medical help.

8. Spill, Leaks and Disposal Procedure

Spills and leaks: Use respiratory protection. Vacuum or scoop up and dispose in appropriate

waste container. Misting spill with water may help to keep airborne dust

levels at a minimum.

Waste Disposal: Waste material can be buried in an approved landfill in accordance to local

environmental regulations. This product is not classified as a hazardous

material.

9. Special Protection

Respirator : Type 3M or equivalent.

Eye Protection: Safety glasses with side shield or goggles.

Gloves : Cloth, rubber or plastic gloves.

Other protection

equipment : Provide adequate exhaust ventilation to meet TLV requirements in the work

place. An exhaust filter may be required to avoid environmental contamination.

10. Special Precautions and Storage

Storage temp.: Ambient.

Average shell life: Unlimited.

Precautions to be taken in handling and storing: Away from food. Store in dry place.

11. Toxicological Information

No information available for this product

12. Ecological Information

No appreciable biocontamination is expected in the environment

13. <u>Disposal Considerations</u>

Material which can not be re-used should be disposed in accordance with federal and local environmental control regulations at an authorised site. This product when discarded as sold is not a hazardous waste.

14. Transportation Information

DOT Shipping Name: None

Technical Shipping Name: Inorganic Oxide DOT Hazardous Classification: Non-Regulated

DOT UN/NA Number:

DOT Labels required:

None

None

DOT Placards required:

Freight Class:

Harmonized Tariff Number:

None

1ron Oxide

2530.90.0015

15. Regulatory Information

This information is provided in conjunction with the ingredient information of Section 2

EINECS: All components of this product are on the European Inventory of Existing

Commercial Chemical Substances (EINECS)

T.S.C.A.: This product is listed on TSC Inventory

OSHA: This product is considered Hazardous by definition of Hazard Communication

Standard (29 CRF 117,302) due to content of crystalline silica above 0.1%

Canadian WHMIS: Contains Crystalline Silica that may cause cancer, High dust levels may

cause skin, eye and upper respiratory tract irritation

CEPA: All Components of this product are on the Domestic Substances List (DSL),

and acceptable for use under the provisions of CEPA.

16. Other Information

MSDS Revisions: No Revisions- Annual review

Prepared By: Evangelos Georgiou, Operations Manager

This product information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best knowledge of United Umber Industries or obtained from sources we believe are accurate. We disclaim any legal responsibility for use or reliance on this information and expressly disclaim that use of this product, either alone or in combination with other materials, will not violate the claims of any patent or rightful claim of any third party. Since you are in control of the application, process and conditions of use of our products, you have an obligation to test the products supplied by us to determine their suitability for the intended processes and uses. Despite this, if liability should be established for any damage, buyer's sole remedy shall be refund of product purchase price from point of purchase. We will, of course, provide consistent quality of our products within the scope of our General Conditions of Sale and Delivery. Before using any chemical, read its label and Material Safety Data Sheet.

10st October, 2010